



链号 Chain No.		节距 Pitch	滚子 直径 Roller diameter	内节 内宽 Width between inner	销轴 直径 Pin diameter	销轴 长度 Width over bearing	连接销 轴长度 Width over connecting	内链板 高度 Inner plates depth	链板 厚度 Plate thickness	抗拉 强度 Ultimate tensile strength	平均抗 拉强度 Average tensile strength	每米 重量 Mass per meter
GB ISO DIN	ANSI	p	d1 max	plates b1 min	d2 max	pins L max	pins Lc max	h2 max	T	Fu min	Fua	q ≈
		mm	mm	mm	mm	mm	mm	mm	mm	kN	kN	kg/m
208A	2040	25.40	7.92	7.85	3.98	17.8	21.7	12.07	1.52	13.9	17.0	0.42
208B		25.40	8.51	7.75	4.45	17.0	20.9	11.80	1.60	17.8	18.4	0.45
210A	2050	31.75	10.16	9.40	5.09	21.8	25.9	15.09	2.03	21.8	28.0	0.73
210B		31.75	10.16	9.65	5.08	19.6	23.7	14.60	1.70	22.2	26.1	0.65
212A	2060	38.10	11.91	12.57	5.96	26.9	31.5	18.10	2.39	31.3	40.0	1.02
212AH	2060H	38.10	11.91	12.57	5.96	30.2	34.8	18.10	3.18	31.3	40.6	1.24
212B		38.10	12.07	11.68	5.72	22.7	27.3	16.10	1.85	28.9	30.6	0.76
216A	2080	50.80	15.88	15.75	7.94	33.5	38.9	24.13	3.18	55.6	66.0	1.70
216AH	2080H	50.80	15.88	15.75	7.94	37.4	42.8	24.13	3.96	55.6	67.8	2.17
216B		50.80	15.88	17.02	8.28	36.1	41.5	21.00	4.15/3.1	60.0	69.2	1.75
220A	2100	63.50	19.05	18.90	9.54	41.1	47.2	30.17	3.96	87.0	104.0	2.55
220B		63.50	19.05	19.56	10.19	43.2	49.3	26.40	4.5/3.5	95.0	101.0	2.62
224A	2120	76.20	22.23	25.22	11.11	50.8	57.4	36.20	4.75	125.0	148.0	4.06
224B		76.20	25.40	25.40	14.63	53.4	60.0	33.40	6.0/4.8	160.0	169.0	4.70
228B		88.90	27.94	30.99	15.90	65.1	72.5	37.00	7.5/6.0	200.0	211.0	6.23
232B		101.60	29.21	30.99	17.81	67.4	75.3	42.20	7.0/6.0	250.0	263.0	6.72