



链号 Chain No.		节距 Pitch	滚子 直径 Roller diameter	内节 内宽 Width between inner	销轴 直径 Pin diameter	销轴 长度 Width over bearing	内链板 高度 Inner plates depth	链板 厚度 Plate thickness	抗拉 强度 Ultimate tensile strength	平均抗 拉强度 Average tensile strength	每米 重量 Mass per meter
GB ISO DIN	ANSI	p	d1 max	plates b1 min	d2 max	pins L max	h2 max	T	Fu min	Fua	q ≈
		mm	mm	mm	mm	mm	mm	mm	kN	kN	kg/m
10A-1	50	15.875	10.16	9.40	5.09	25.9	15.09	2.03	21.8	28.0	1.02
10A-2	50-2	15.875	10.16	9.40	5.09	44.0	15.09	2.03	43.6	55.0	2.00
10A-3	50-3	15.875	10.16	9.40	5.09	62.0	15.09	2.03	65.4	74.0	3.09
12A-1	60	19.05	11.91	12.57	5.96	31.5	18.10	2.39	31.3	40.0	1.50
12A-2	60-2	19.05	11.91	12.57	5.96	54.4	18.10	2.39	62.6	80.0	2.92
12A-3	60-3	19.05	11.91	12.57	5.96	77.2	18.10	2.39	93.9	106.0	4.54
16A-1	80	25.40	15.88	15.75	7.94	38.9	24.13	3.18	55.6	66.0	2.60
16A-2	80-2	25.40	15.88	15.75	7.94	68.1	24.13	3.18	111.2	135.0	5.15
16A-3	80-3	25.40	15.88	15.75	7.94	97.3	24.13	3.18	166.8	188.5	7.89
20A-1	100	31.75	19.05	18.90	9.54	47.2	30.17	3.96	87.0	104.0	3.91
20A-2	100-2	31.75	19.05	18.90	9.54	83.1	30.17	3.96	174.0	208.0	7.80
20A-3	100-3	31.75	19.05	18.90	9.54	119.1	30.17	3.96	261.0	294.0	11.77
24A-1	120	38.10	22.23	25.22	11.11	57.4	36.20	4.75	125.0	148.0	5.62
24A-2	120-2	38.10	22.23	25.22	11.11	102.9	36.20	4.75	250.0	299.0	11.70
24A-3	120-3	38.10	22.23	25.22	11.11	148.3	36.20	4.75	375.0	415.0	17.53
28A-1	140	44.45	25.40	25.22	12.71	62.3	42.23	5.56	170.0	201.0	7.50
28A-2	140-2	44.45	25.40	25.22	12.71	111.0	42.23	5.56	340.0	406.0	15.14
28A-3	140-3	44.45	25.40	25.22	12.71	159.8	42.23	5.56	510.0	564.0	22.20
32A-1	160	50.80	28.58	31.55	14.29	73.4	48.26	6.35	223.0	265.0	10.10
32A-2	160-2	50.80	28.58	31.55	14.29	132.1	48.26	6.35	446.0	534.0	20.14
32A-3	160-3	50.80	28.58	31.55	14.29	190.8	48.26	6.35	669.0	742.0	30.02
36A-1	180	57.15	35.71	35.48	17.46	83.0	54.30	7.14	281.0	325.0	13.95
36A-2	180-2	57.15	35.71	35.48	17.46	149.1	54.30	7.14	562.0	660.0	27.62
36A-3	180-3	57.15	35.71	35.48	17.46	215.1	54.30	7.14	843.0	934.0	38.22
40A-1	200	63.50	39.68	37.85	19.85	90.5	60.33	7.92	347.0	410.0	16.86
40A-2	200-2	63.50	39.68	37.85	19.85	162.1	60.33	7.92	694.0	834.0	33.42
40A-3	200-3	63.50	39.68	37.85	19.85	233.7	60.33	7.92	1041.0	1157.0	50.05
48A-1	240	76.20	47.63	47.35	23.81	106.0	72.39	9.52	500.0	591.0	23.60
48A-2	240-2	76.20	47.63	47.35	23.81	193.9	72.39	9.52	1000.0	1193.0	47.35
48A-3	240-3	76.20	47.63	47.35	23.81	281.8	72.39	9.52	1500.0	1669.0	72.04