



链号 Chain No.	节距 Pitch	滚子 直径 Roller diameter	内节 内宽 Width between inner plates	销轴直径 Pin diameter	销轴长度 Width over bearing pins		内链板高度 Inner Plates depth	链板厚度 Plate thickness	侧弯半径 Side bow radius	每米重量 Mass per meter
Dongfeng	p	d1 max	b1 min	d2 max	L max	Lc max	h2 max	t/T	R	q ≈
	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg/m
40SB	12.70	7.92	7.85	3.96	17.8	21.7	12.07	1.52	350	0.80
50SB	15.875	10.16	9.40	4.37	21.8	25.9	15.09	2.03	400	1.09
60SB	19.05	11.91	12.57	5.34	26.9	31.5	18.08	2.39	500	1.54
80SB	25.40	15.88	15.75	7.19	33.5	38.9	24.13	3.18	711	2.60
08BSB	12.70	8.51	7.75	3.97	17.0	20.9	11.81	1.60	400	0.70
10BSB	15.875	10.16	9.65	4.50	19.6	23.7	14.73	1.70	400	0.93
12BSB	19.05	12.07	11.68	5.12	22.7	27.3	16.13	1.85	500	1.16
16BSB	25.40	15.88	17.02	7.90	36.1	41.5	21.08	4.15/3.1	500	2.53

注意：所有短节距滚子链的附件类型都运用于上述这类链条
Note: All kinds of attachment types for short pitch roller chains are available for these chains above.