



东风链号 Dongfeng Chain No.	节距 Pitch	滚子直径 Roller diameter	内节内宽 Width between inner plates	链板厚度 Plate thickness	链板高度 Inner plates depth	销轴尺寸参数 Pin dimension				外滚轮尺寸 Outboard roller	
						d	L1	L2	L3	Ds	Hs
	p	d1 max	b1 min	T	h2 max	d	L1	L2	L3	Ds	Hs
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
C2040SR	25.40	7.95	7.85	1.52	12.07	3.96	8.30	17.70	19.90	15.88	7.80
C2042SR		15.88						23.10	24.50	23.00	13.00
C2050SR	31.75	10.16	9.43	2.03	15.09	5.08	10.30	21.50	23.50	19.05	9.40
C2052SR		19.05						25.30	27.00	27.00	13.00
C2060SR	38.10	11.91	12.57	3.26	18.10	5.94	14.95	29.65	32.05	22.23	12.60
C2062SR		22.23						30.05	32.45	30.00	13.00
C2080SR	50.80	15.88	15.75	4.00	24.13	7.92	18.30	36.65	39.65	28.58	15.80
C2082SR		28.58									
C2100SR	63.50	19.05	18.90	4.80	30.17	9.53	22.05	44.20	47.30	39.69	19.00
C2102SR		39.67									

注：按客户要求，短节距和双节距链的顶滚轮材料均是可以采用工程塑料或钢。

Note: According to customer require, top roller material of short pitch and double pitch chains may both be engineering plastics or steel.