



东风链号	节距 Pitch	滚子直径 Roller diameter	内节内宽 Width between inner plates	链板厚度 Plate thickness	链板高度 Inner plates depth	销轴尺寸参数 Pin dimensions				侧滚轮尺寸 Side roller	
Dongfen Chain No.	p	d <sub>1</sub> max	b <sub>1</sub> min	T	h <sub>2</sub> max	d	L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	Ds	Hs
	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
40SR	12.70	7.95	7.85	1.52	12.07	3.96	8.30	17.70	19.90	15.88	7.80
50SR	15.88	10.16	9.43	2.03	15.09	5.08	10.30	21.50	23.50	19.05	9.40
60SR	19.05	11.91	12.57	2.39	18.10	5.94	12.95	27.95	30.35	22.23	12.60
80SR	25.40	15.88	15.75	3.18	24.13	7.92	16.35	35.05	37.95	28.58	15.80
100SR	31.75	19.05	18.90	3.96	30.17	9.53	20.55	42.55	45.65	39.69	19.00

### 双节距顶滚轮输送链

Double pitch top roller conveyor chain

这种链条的图形和符号与上页的相同

The figure and symbols of this chain are as same as those of the chain on above page.

东风链号 Dongfeng Chain No.	节距 Pitch P	内节内宽 Width between inner plates b <sub>1</sub>	滚子直径 Roller diameter d <sub>1</sub>
	mm	mm	mm
C2040TR	25.40	7.95	7.94,15.88(L)
C2050TR	31.75	9.53	10.16,19.05(L)
C2060TR	38.10	12.70	11.91,22.23(L)
C2080TR	50.80	15.88	15.88,28.58(L)
C2100TR	63.50	19.05	19.05,39.69(L)

销轴尺寸 Pin dimension			链板尺寸 Plate dimension		抗拉强度 Ultimate tensile strength	附件尺寸 Attachment dimensions						每米重量 Mass per meter
d	L	Lc	h <sub>2</sub>	T	Fu	D <sub>F</sub>	Cs	Xs	N	l	d <sub>3</sub>	kg/m
mm	mm	mm	mm	mm	kgf	mm	mm	mm	mm	mm	mm	
3.97	16.40	17.45	12.07	1.52	1.700	15.88	12.70	17.45	9.5	13.20	4.03	1.30
5.09	20.60	22.15	15.09	2.03	2.800	19.05	15.90	22.25	12.7	16.20	5.20	1.90
5.96	25.50	27.30	18.10	2.39	4.100	22.23	18.30	26.25	15.9	20.60	6.10	2.90
7.94	32.46	36.05	24.13	3.18	7.000	28.58	24.60	34.15	19.1	25.70	8.07	4.80
9.54	39.60	43.40	30.17	3.96	11.000	36.69	31.80	44.50	25.4	31.10	9.73	7.90