



链号 Chain No.		p	b <sub>1</sub>	d <sub>2</sub>	L <sub>3</sub>		L	
			min	max	X型 Xtype	Y型 Ytype	X型 Xtype	Y型 Ytype
ISO DIN	ANSI	mm	mm	mm	mm	m	mm	m
06C	35	9.525	4.68	3.60	12.30	10.20	23.40	21.90
08A	40	12.700	7.85	3.98	16.50	10.20	32.30	26.30
10A	50	15.875	9.40	5.09	20.60	12.70	39.90	32.60
12A	60	19.050	12.57	5.96	25.70	15.20	49.80	40.00
16A	80	25.400	15.75	7.94	32.20	20.30	62.70	51.70
20A	100	31.750	18.90	9.54	39.10	25.40	77.00	63.8
24A	120	38.100	25.22	11.11	48.90	30.50	96.30	78.6
28A	140	44.450	25.22	12.71	—	35.60	—	87.5
32A	160	50.800	31.55	14.29	—	40.60	—	102.6
*06B		9.525	5.72	3.28	12.2	—	23.8	—
08B		12.700	7.75	4.45	15.50	—	31.00	—
10B		15.875	9.65	5.08	18.50	—	36.20	—
12B		19.050	11.68	5.72	21.50	—	42.20	—
16B		25.400	17.02	8.28	34.50	—	68.00	—
20B		31.750	19.56	10.19	39.40	—	79.70	—
24B		38.100	25.40	14.63	51.40	—	101.80	—

\* 直板链 Straight side plates.

\*\*X型的L值与双排滚子链的销轴长相同

The L value of X type is as same as the pin length of doubling roller chains.