



顶滚轮配置 Top roller spacing
 I型 逐节配置 Type I Every link spacing
 II型 隔节配置 Type II Every Other link spacing

链号 Chain No.	节距 Pitch	内节内宽 Width between inner plates	滚子直径 Roller diameter	销轴尺寸 Pin dimension			链板尺寸 Plate dimension		排距 Transverse pitch	抗拉强度 Ultimate tensile strength
	P	b ₁	d ₁	d	L	L _c	h ₂	T	C	F _u
Dongfeng	mm	mm	mm	mm	mm	mm	mm	mm	mm	kgf
40TR	12.70	7.95	7.94	3.97	16.40	17.45	12.00	1.52	—	1.700
50TR	15.875	9.53	10.16	5.09	20.60	22.15	15.00	2.03	—	2.800
60TR	19.05	12.70	11.91	5.96	25.50	27.30	18.10	2.39	—	4.100
80TR	25.40	15.88	15.88	7.94	32.46	36.05	24.10	3.18	—	7.000
100TR	31.75	19.05	19.05	9.54	39.60	43.40	30.10	3.96	—	11.000
40TR-2	12.70	7.95	7.94	3.97	30.80	31.85	12.00	1.52	14.38	3.440
50TR-2	15.875	9.53	10.16	5.09	38.70	40.25	15.00	2.03	18.11	3.200
60TR-2	19.05	12.70	11.91	5.96	48.30	50.10	18.10	2.39	22.78	4.400
80TR-2	25.40	15.88	15.88	7.94	60.18	64.59	24.10	3.18	29.29	7.500
100TR-2	31.75	19.05	19.05	9.54	75.40	79.20	30.10	3.96	35.76	11.500

链号 Chain No.	附件尺寸 Attachment dimensions									每米重量 Mass per meter	
	Df		Cs	N	Xs	XSA	M	I	I ₁		d ₃
I	II	mm								mm	
Dongfeng	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg/m
40TR	11.0	15.88	12.70	9.50	17.45	17.40	9.50	13.20	—	4.03	1.30
50TR	15.0	19.05	15.90	12.70	22.25	23.05	12.70	16.20	—	5.20	1.90
60TR	18.0	22.23	18.30	15.90	26.25	26.85	15.90	20.60	—	6.10	2.90
80TR	24.0	28.58	24.60	19.10	34.15	35.45	19.10	25.70	—	8.07	4.80
100TR	30.0	36.69	31.80	25.40	44.50	44.00	25.40	31.10	—	9.73	7.90
40TR-2	11.0	15.88	12.70	9.50	17.45	17.40	9.50	—	28.30	3.97	2.60
50TR-2	15.0	19.05	15.90	12.70	22.25	23.05	12.70	—	34.30	5.20	3.80
60TR-2	18.0	22.23	18.30	15.90	26.25	26.85	15.90	—	43.40	6.10	5.80
80TR-2	24.0	28.58	24.60	19.10	34.15	35.45	19.10	—	55.00	8.07	9.60
100TR-2	30.0	36.69	31.80	25.40	44.50	44.00	25.40	—	66.90	9.73	15.80

注：按客户要求，短节距和双节距链的顶滚轮材料均是可以采用工程塑料或钢。
 Note: According to customer require, top roller material of short pitch and double pitch chains may both be engineering plastics or steel.