



链号 Chain No.	节距 Pitch	滚子 直径 Roller diameter	内节内宽 Width between inner plates	销轴 直径 Pin diameter	销轴 长度 Pins length		内链板 高度 Inner plates depth	链板 厚度 Plate thickness	抗拉强度 Ultimate tensile strength	每米 重量 Mass per meter
GB ISO	p	d ₁ max	b ₁ min	d ₂ max	L max	L _c max	h ₂ max	T	F _u min	q ≈
Dongfeng	mm	mm	mm	mm	mm	mm	mm	mm	kN	kg/m
S32	29.21	11.43	15.88	4.45	26.7	28.8	13.20	1.80	8.00	0.86
S32-H									17.50	
S42	34.93	14.27	19.05	7.00	34.3	37.0	19.80	2.80	26.70	1.60
S42-H									41.00	
S45	41.40	15.24	22.23	5.72	37.7	40.4	17.30	2.80	17.80	1.66
S45-H									32.00	
S52	38.10	15.24	22.23	5.72	37.7	40.4	17.30	2.80	17.80	1.68
S52-H									32.00	
S55	41.40	17.78	22.23	5.72	37.7	40.4	17.30	2.80	17.80	1.80
S55-H									32.00	
S62	41.91	19.05	26.20	5.72	40.3	43.0	17.30	2.50	26.70	1.87
S62-H									32.00	
S77	58.34	18.26	22.23	8.90	43.2	46.4	26.20	4.00	44.50	2.66
S77-H									80.00	
S88	66.27	22.86	28.58	8.90	49.8	53.0	26.20	4.00	44.50	3.25
S88-H									80.00	
C550	41.40	16.87	19.81	7.19	35.2	38.2	20.20	2.00	39.10	1.95
C550-H									57.80	
C620	42.01	17.91	24.51	7.19	41.3	45.0	20.20	4.00	39.10	2.35
C620-H									57.80	

注:H系列的尺寸, 包括附件尺寸, 与普通系列的尺寸相同, 但材料和热处理不同。

The dimensions of H series are as same as of general series, including attachment dimensions, but both of material and heat treatment.