



链号 Chain No.	节距 Pitch	滚子 直径 Roller diameter	内节内宽 Width between inner plates	销轴 直径 Pin diameter	销轴长度 Pin length		内链板 高度 Inner plates depth	链板 厚度 Plate thickness	排距 Transverse pitch	抗拉强度 Ultimate tensile strength	每条 长重 Mass per piece
					L	Lc					
Dengfng	p mm	d1 max mm	b1 min mm	d2 max mm	max mm	max mm	h2 max mm	T max mm	pt mm	Fu min kN/lb	q ≈ kg/pc
4012	12.70	7.92	7.85	3.98	32.3	36.2	12.07	1.52	14.38	27.8	0.16
4014	12.70	7.92	7.85	3.98	32.3	36.2	12.07	1.52	14.38	27.8	0.19
4016	12.70	7.92	7.85	3.98	32.3	36.2	12.07	1.52	14.38	27.8	0.21
5014	15.875	10.16	9.40	5.09	39.9	44.0	15.09	2.03	18.11	43.6	0.49
5016	15.875	10.16	9.40	5.09	39.9	44.0	15.09	2.03	18.11	43.6	0.56
5018	15.875	10.16	9.40	5.09	39.9	44.0	15.09	2.03	18.11	43.6	0.63
6018	19.05	11.91	12.57	5.96	49.8	54.4	18.10	2.39	22.78	62.6	1.00
6020	19.05	11.91	12.57	5.96	49.8	54.4	18.10	2.39	22.78	62.6	1.11
6022	19.05	11.91	12.57	5.96	49.8	54.4	18.10	2.39	22.78	62.6	1.22
8018	25.40	15.88	15.75	7.94	62.7	68.1	24.13	3.18	29.29	111.2	2.35
8020	25.40	15.88	15.75	7.94	62.7	68.1	24.13	3.18	29.29	111.2	2.62
8022	25.40	15.88	15.75	7.94	62.7	68.1	24.13	3.18	29.29	111.2	2.88
10018	31.75	19.05	18.90	9.54	77.0	83.1	30.17	3.96	35.76	174	4.95
10022	31.75	19.05	18.90	9.54	77.0	83.1	30.17	3.96	35.76	174	4.95
12018	38.10	22.23	25.22	11.11	96.3	102.9	36.20	4.75	45.44	250	8.14
12022	38.10	22.23	25.22	11.11	96.3	102.9	36.20	4.75	45.44	250	8.14