



链号 Chain No.	优选滚子型式 Optimal roller types	节距 Pitch							滚子直径 Roller diameter	销轴直径 Pin diameter	套筒直径 Bush diameter
		p							d1 max	d2 max	d3 max
DIN		mm	mm	mm	mm	mm	mm	mm	mm	mm	
FVT40	A	50	63	80	100	125			32	10	15
FVT63	B	63	80	100	125	160			40	12	18
FVT90	F	63	80	100	125	160	200	250	48	14	20
FVT112	A	100	125	160	200	250			55	16	22
FVT140	B	100	125	160	200	250			60	18	25
FVT180	C	125	160	200	250	315			70	20	30
FVT250	F	160	200	250	315				80	26	36
FVT315	E	160	200	250	315	400			90	30	42

链号 Chain No.	内节内宽 Width between inner plates	销轴长度 Pin length		链板高度 Plate depth		链板厚度 Plate thickness	抗拉强度 Ultimate tensile strength
	b1 min	L max	Lc max	h2 max	h max	T max	Fu min
DIN	mm	mm	mm	mm	mm	mm	kN/lb
FVT40	18.0	36.0	39.0	35.0	22.5	3.0	40.0/9091
FVT63	22.0	45.0	48.5	40.0	25.0	4.0	63.0/14317
FVT90	25.0	53.0	56.5	45.0	27.5	5.0	90.0/20453
FVT112	30.0	62.0	66.0	50.0	30.0	6.0	112.0/25452
FVT140	35.0	67.0	71.5	60.0	37.5	6.0	140.0/31815
FVT180	45.0	86.0	92.0	70.0	45.0	8.0	180.0/40908
FVT250	55.0	97.0	103.5	80.0	50.0	8.0	250.0/56817
FVT315	65.0	113.0	126.5	90.0	55.0	10.0	315.0/71591

注：带空心销轴的FVT系列链条，可按用户定货。

Note: The FVT series chains with hollow pins may be ordered specially, according to customer require.