



链号 Chain No.	滚子 型式 Roller	节距 Pitch					滚子直径 Roller diameter	销轴直径 Pin diameter	套筒直径 Bush diameter
GB ISO DIN	type	P					d1 max	d2 max	d3 max
		mm	mm	mm	mm	mm	mm	mm	mm
MT20	P	40	50	63	80	100	25	6.0	9.0
MT28		50	63	80	100	125	30	7.0	10.0
MT40		63	80	100	125	160	36	8.5	12.5
MT56		63	80	100	125	160	42	10.0	15.0
MT80		80	100	125	160	200	50	12.0	18.0
MT112	P C	80	100	125	160	200	60	15.0	21.0
MT160		100	125	160	200	250	70	18.0	25.0
MT224	C	125	160	200	250	315	85	21.0	30.0
MT315		160	200	250	315	400	100	25.0	36.0
MT450		200	250	315	400	500	120	30.0	42.0

链号 Chain No.	内节内宽 Width between inner plates	销轴长度 Pin length	链板高度 Plate depth		链板厚度 Plate thickness	抗拉强度 Ultimate tensile strength
GB ISO DIN	b1 min	L max	h2 max	h max	T max	Fu min
	mm	mm	mm	mm	mm	kN/lb
MT20	16.0	35.0	25.0	16.0	2.5	20.0/4545
MT28	18.0	40.0	30.0	20.0	3.0	28.0/6364
MT40	20.0	45.0	35.0	22.5	3.5	40.0/9091
MT56	24.0	52.0	45.0	30.0	4.0	56.0/12727
MT80	28.0	62.0	50.0	32.5	5.0	80.0/18182
MT112	32.0	73.0	60.0	40.0	6.0	112.0/25454
MT160	37.0	85.0	70.0	45.0	7.0	160.0/36364
MT224	43.0	98.0	90.0	60.0	8.0	224.0/50909
MT315	48.0	112.0	100.0	65.0	10.0	315.0/71591
MT450	56.0	135.0	120.0	80.0	12.0	450.0/102272

注：这种高链板也适用于空心销轴，构成MCT28、MCT56、MCT112和MCT224。

Note: This kind of deep plates is also suitable for MC series to construct MCT28, MCT56, MCT112 and MCT224.